



HRC-P6500D

24

IP

360

100m—2000m

24

HRC-P6500D

1.

2.

24

3.

4.

5.

6.

7.

13

8.

GIS

10.

11. IP

12. 1 RJ45

PTZ

13. IP67

		HRC-P6500D
3D		1/2.8" / 1/3" CMOS
		130 /200 /300 /500
		1920x1080
		4.7mm - 94mm/4.3mm 129mm/4.3mm 164mm
		20X/30X/38X
		F1.5-F5.0
		0.01Lux/ 0.001Lux
		H.265/H.264/MJPEG
		32kbps-12Mbps
		25/30 fps
		50dB
		IR
		IR
		/
		384x288/640x480
		25mm/50mm
		17um
		8- 14um
		30mk at f/1.0 300K
		-20 350 2000
		2 2%

		HRC-P6500D
		13
		HDR
		IDE
		1-4
		+
		360°
		0.1° 165°/s
		-30° +93°
		0.1° 100°/s
		256
		256
		4 10
		RJ45 10Base-T/100Base-TX
		onvif GB28281
		TCP/IP HTTP DHCP DNS DDNS RTP RTSP PPPoE SMTP NTP UPnP SNMP FTP 802.1x QoS HTTPS IPv6
	IP	
		micro SD
		AC24V 50Hz
		36W
		IP67 4000V
		-45 70 90%
		310mm ×210mm
		6.9Kg



C 13

0755-86518800 0755-86518855
QQ 76024879
sales@ huaruicom.com
www.huaruicom.com



15333833961
13632702325

13632702323
0551-65837321

15104440003
029-82098966

15889666061
028-86658015

027-87879966
0871-68358002

021-63550300
15978139595