

HRC-P6200

HRC-P6200

10.

11. IR

IR

12.

13.

14. 360°

-45°-45°

15.

16. 255

0.01° 8

17. IP67


18.

GIS

19. IP67

		HRC-P6200
		1/3 1/2 CMOS
		130 /200 /300 /500 /1000
		:0.005 Lux @ (F1.2,AGC ON) :0.0005Lux @ (F1.2,AGC ON)
		ICR
		,IP
		1920*1080
		6-60mm/8.5-85mm/7.5-128mm/10-210mm/10-330mm/10-360mm/15.6-500mm/12.5-750mm/12.5-770mm/12.5-1250mm
		F1.0-F5.6

		HRC-P6200
		A 20000
		810nm 808nm/915nm/950/975nm
		0.2° ~ 20°
		8W/10W/15W/20W/25W/30W
		/
		0.01
		4mm
		50kg
		360° -45° 45° -80° ~ 80°
		0.01°/ 30°/ 0.01°/ 20°/
		256
		RS-422/RS-485
		PELCO-D/P
		1 RJ45 10M / 100M/1000M
		16 10
		DC24V
		-45 70
		8000V
		42Kg
		100W 150W
		IP67
		657(L)x378(W)x610(H)



C 13

0755-86518800 0755-86518855  
13922881698  
QQ 76024879  
sales@ huaruicom.com  
www.huaruicom.com



13922881698  
18665360602

13538144380  
13538144385

13632702323

13538144385

15104440003

18823877073